MICROSONIC® CUSTOM EARMOLDS SELECTION GUIDE



Custom earmold is an essential component of any hearing aid device to obtain 100% of desired acoustic performance. Nevertheless, selecting the optimum earmold configuration can be difficult. The following information intends to help you selecting appropriate earmold style, material, and acoustic options. Please refer to Microsonic Custom Earmold Manual for further reading.

OCCLUDING vs. NON-OCCLUDING (OPEN)

Occluding earmolds are recommended for most severe to profound hearing loss and for all power BTE hearing aids. Although, some earmold styles are recommended by default for certain types of loss, keep in mind that every case is different.

Non-occluding earmolds feature a small outside diameter canal portion to allow amplified sound to pass around the earmold as well as go through the tubing. They offer the patient a more pleasing sound by providing an "overlay" of amplification on the natural hearing.

Non-occluded earmolds are also recommended for patients who have a chronic drainage problem, since aeration of the ear canal is allowed.

MICROSONIC CUSTOM BTE EARMOLD STYLES			
DESCRIPTIVE PICTURE	STYLE NUMBER	STYLE NAME	SPECIAL NOTES
0	#1	REGULAR	Occluding All Materials EXCEPT Platinum Cure Silicones (M25,M35,M45, SlikFit™) Used with external receiver that snaps into earmold
6	#1A	REGULAR W/TUBING	Occluding All Materials Used with head-worn instruments
	#2	SKELETON	Occluding All Materials Open space in concha for appearance
	#2A	¾ SKELETON	Occluding
	#2B	½ SKELETON	All Materials Recommended Skeleton style for dexterity issues
3	#3	SEMI-SKELETON	Occluding All Materials Recommended for ears with flat concha rim to avoid earmold sticking out from ear



MICROSONIC CUSTOM BTE EARMOLD STYLES			
DESCRIPTIVE PICTURE	STYLE NUMBER	STYLE NAME	SPECIAL NOTES
	#4	CANAL	Occluding All Materials Fills only the canal portion of the ear Helix and concha areas are removed Suitable when retention is not an issue
	#5	CANAL-LOK	Occluding All Materials Similar to canal style, easier to insert and remove
	#5A	CANAL-LOK W/HELIX	Occluding All Materials Recommended for ears with flat concha rim to avoid earmold sticking out from ear. Provides additional retention without sacrificing the cosmetic advantages of the Canal-Lok style
4	#5L	CANAL-LONG LOK	Occluding All Materials Provides <u>additional</u> retention without sacrificing the cosmetic advantages of the Canal-Lok style
	#6	SHELL	Occluding All Materials Deeply shelled out in the concha area Used when acoustic seal is an essential factor
	#6A	MICRO-SHELL	Occluding All Materials Shallowed Concha Shell with improved appearance and comfort
	#7	CANAL-SHELL (Half-Shell)	Occluding All Materials
	#7A	¾ SHELL	Performs as Shell style Ideal for dexterity issues (easy insertion & removal)
3	#16	CROS A (no vent)	Non-Occluding Hard material only Designed for CROS and many IROS fittings Canal-Lok style with longer lok Long Canal Significantly reduction in frequencies below 1000 Hz
3	#17	CROS B (no vent)	Non-Occluding Hard material only Designed for CROS and many IROS fittings. Shorter canal. Significantly reduction in frequencies below 1000 Hz



MICROSONIC CUSTOM BTE EARMOLD STYLES			
DESCRIPTIVE PICTURE	STYLE NUMBER	STYLE NAME	SPECIAL NOTES
3	#18	CROS C (no vent)	Non-Occluding All Materials Recommended for attaching the offside microphone or transmitter in a BTE CROS or BICROS fitting
0	#21A	ADVANCED DESIGN FREE FIELD (with SAV)	Non-Occluding All Materials Minimum occlusion Seals canal entrance while leaving the canal itself unoccluded Eliminates feedback
	#21B	ADVANCED DESIGN FREE FIELD (with SAV)	Non-Occluding All Materials Moderate occlusion Seals canal entrance while leaving the canal itself unoccluded Eliminates feedback
	#21C	ADVANCED DESIGN FREE FIELD (with SAV)	Non-Occluding All Materials Moderate occlusion Seals canal entrance while leaving the canal itself unoccluded Eliminates feedback
	#41A	CANAL-LOK ADV. DESIGN FREE FIELD (with SAV)	Non-Occluding All Materials Acoustically identical to #21A
	#41B	CANAL-LOK ADV. DESIGN FREE FIELD (with SAV)	Non-Occluding All Materials Acoustically identical to #21B
	#41C	CANAL-LOK ADV. DESIGN FREE FIELD (with SAV)	Non-Occluding All Materials Acoustically identical to #21C
5	#34	HOLLOW CANAL	Soft Materials For severe hearing losses with excessive mandibular action
2	#OF2	OPEN-FIT SKELETON (w/IROS) (w/slim tube or RIC)	Non-Occluding Available in all materials. Provides largest vent possible. For maximum comfort with own voice. SAV is optional



MICROSONIC CUSTOM BTE EARMOLD STYLES			
DESCRIPTIVE PICTURE	STYLE NUMBER	STYLE NAME	SPECIAL NOTES
	#OF4	OPEN-FIT CANAL (w/IROS) (w/slim tube or RIC)	Non-Occluding Available in all materials. Provides largest vent possible. For maximum comfort with own voice. SAV is optional
To the same of the	#OF5	OPEN-FIT CANAL-LOK (w/IROS) (w/slim tube or RIC)	Non-Occluding Available in all materials. Provides largest vent possible. For maximum comfort with own voice. SAV is optional
	#OF7	OPEN-FIT CANAL-SHELL (w/IROS) (w/slim tube or RIC)	Non-Occluding Available in all materials. Provides largest vent possible. For maximum comfort with own voice. SAV is optional
	#OF21	OPEN-FIT ADV DESIGN FREE FIELD (w/SAV) (w/slim tube or RIC)	Non-Occluding Available in all materials for use with slim tubes or RIC.
6	#SL2	SLIM-FIT SKELETON (specify vent size) (specify receiver model)	Occluding Recommended for RIC . Soft materials ONLY
B	#SL4	SLIM-FIT CANAL (specify vent size) (specify receiver model)	Occluding Recommended for RIC . Soft materials ONLY
4	#SL5	SLIM-FIT CANAL-LOK (specify vent size) (specify receiver model)	Occluding Recommended for RIC . Soft materials ONLY

CLASSICAL MODIFICATION AND EFFECT CHART

	Modification	Effect on Low	Effect on	Effect on	Effect on High
		Frequencies	Frequencies	Frequencies	Frequencies
		<750 Hz	750 - 1500 Hz	1500 - 3000 Hz	>3000 Hz
TUBING	Larger I.D. Tubing & Horn Tubing	Negligible	Moves peak to higher frequency	Increases height of peak and moves to higher frequency	Increases
DIAMETER	DIAMETER Smaller I.D. Tubing	May reduce below 1,000 Hz	Moves peak to lower frequency	Reduces height of peak and moves to lower frequency	Large reduction
TUBING LENGTH	Longer Tubing	Increases	Moves peak to lower frequency	Moves peak to lower frequency	Negligible
TOBING LENGTH	Shorter Tubing	Slightly decreases	Moves peak to higher frequency	Moves peak to higher frequency	Negligible
LENGTH OF	Longer canal		Increases level of	of response curve	
EARMOLD CANAL	Shorter canal		Decreases level	of response curve	
BORE DIAMETER	Larger diameter bore through earmold canal*	Negligible	Moves peak to higher frequency	Moves peak to higher frequency	Increases
BORE DIAIVIETER	Smaller diameter through earmold canal*	Negligible	Moves peak to lower frequency	Moves peak to lower frequency	Decreases
BORE LENGTH	Longer bore through earmold canal*	Slightly increases	Moves peak to lower frequency	Moves peak to lower frequency	Decreases
	Shorter bore through earmold canal	Slightly decreases	Moves peak to higher frequency	Moves peak to higher frequency	Increases
	Small Vent (.031"/0.8mm)**	Negligible	Negligible	Negligible	Negligible
VENTING	Medium Vent (.064"/1.6mm)**	Decreases	Increases peak height	Negligible	Negligible
	Large Vent (.094"/2.4mm)**	Decreases	Increases peak height	Negligible	Negligible
NON-OCCLUDING MOLD	Non-Occluding Mold	Eliminates	Moves peak to higher frequency and increases height	Increases peak height	Negligible
OPEN VENT MOLD	Open-Vented (High Frequency) Mold	Decreases	Reduces peak height	Reduces peak height	Negligible
FILTER INSERTS	Filter Insert at Hearing Aid Nub	Negligible	Reduces peak height	Reduces peak height	Negligible
FILTER INSERTS	Filter Insert at Earmold Tip	Slightly decreases	Large reduction	Large reduction	Decreases

NOTE: Because of wide variation in earphone types and internal acoustical systems in hearing aids, this chart must be considered as a guide for average conditions.

^{**} Vents of short lengths are more effective in reducing low frequency response. Gain must be limited with larger size vents to avoid feedback.



^{*} Applies to earmolds for conventional earphones

MICROSONIC® Earmold Materials

ACRYLIC MATERIAL			
Acrylic	► Hard ► Hypoallergenic ► Ideal for soft/thin skin		
Super Alerite	► Hard ► Hypoallergenic ► Heat-cure ► Ideal for soft/thin skin ► Recommended for severe skin problems		
	VINYL MATERIALS		
Synth-A-Flex	 Super soft (Shore A 35) Modifiable Comfortable Not for long-term use (up to 1 year) 		
Vinylflex	► Hard ► Flexes with body heat ► Hypoallergenic		
	SILICONE MATERIALS		
M25	 ▶ Platinum cure ▶ Super soft (Shore A 25) ▶ Hypoallergenic ▶ Antibacterial ▶ Superior comfort ▶ Recommended for adults/pediatrics ▶ Tolerance for growth ▶ Multi-colors ▶ Platinum cure ▶ Soft (Shore A 35) ▶ Hypoallergenic 		
M35 (also known as M2000) DEFAULT SILICONE MATERIAL	► Antibacterial ► Recommended for adults/pediatrics, power BTE ► Multi-colors		
M45	 ▶ Platinum cure ▶ Semi-soft (Shore A 45) ▶ Hypoallergenic ▶ Antibacterial ▶ Recommended for adults/pediatrics, power BTE ▶ Multi-colors 		
SlikFit™	 ▶ Platinum cure ▶ Soft (Shore A 35) ▶ Hypoallergenic ▶ Antibacterial ▶ Recommended for adults/pediatrics, power BTE ▶ Silky Matte ▶ Easy insertion ▶ Multi-colors 		
Medi-Sil	 ▶ Heat cure ▶ Semi-soft (Shore A 50) ▶ Hypoallergenic ▶ Recommended for adults/seniors, power BTE ▶ Recommended for sensitive skins ▶ Silky Texture 		
Medi-Sil Clear	► Same as Medi-Sil.► Recommended for severe allergic cases		
Medi-Sil Plus	► Sh. A 50 concha with Sh. A 30 canal ► Recommended for sensitive skins, senior citizens, power BTE ► Silky Texture		
COMBIN	ATION MATERIALS (Canal Additives)		
Super Alerite Body w/Silky Silicone Canal	► Hard body with flexible Medi-Sil Canal ► Heat cure materials ► Recommended for soft/thin skin and severe allergic cases ► Ideal for individuals w/dexterity issues and excessive mandibular movement.		
Acrylic Body w/Synth-A-Flex Canal	► Hard body with super soft Canal		



	OTHER MATERIALS
Polyethylene	► Hard ► Hypoallergenic ► Recommended for most severe allergic cases ► Opaque pink only
Neon-Lite™	 Default swim plug material ► Floating Semi-soft (Shore A 45) ► Platinum Cure Silicone Multi-colors (opaque only)
PassGuard™	 ► Hearing Protection ► NRR 27 dB, Mean 38 dB, Attenuation up to 47 dB ► Perfect for high impact noise ► Permits hearing conversation ► Semi-soft (Shore A 45) ► Platinum Cure Silicone ► Hypoallergenic ► Multi-colors (opaque only)
SoftGuard™	 ► Hearing Protection ► Superior acoustic seal ► NRR 26 dB, Mean 40 dB, Attenuation up to 48 dB ► Perfect for high impact noise ► Permits hearing conversation ► Soft (Shore A 30) ► Platinum Cure Silicone ► Hypoallergenic ► Multi-colors (opaque only)